

# High Voltage Silicon Diodes for Micro-wave oven

Reverse Voltage – 12KV Forward Current –500mA

#### FEATURES


High reliability

#### **Applications**

Rectification for high voltage power supply of magnetron in Micro wave oven and others

#### **MECHANICAL DATA**

- +Case: Molded Plastic Body
- +Epoxy meets UL 94V-0 flammability rating
- •Terminals: Pure tin plated leads, solderable per J-STD-002and JESD22-B102, E3 suffix for consumer grade, meet JESD201class 1A whisker test.
- Polarity: Color band denotes cathode end



Marking Code			
CL04-12	YFW CL04-12		

### Maximum rating (Ta=25°C unless otherwise noted)

Parameter		Symbol	CL04-12	Unit
Repetitive peak reverse voltage		V <sub>RRM</sub>	12	kV
Average forward current	60H <sub>z</sub> half-sine wave, Resistance load, Ta≤60°C	I <sub>F(AV)</sub>	500	mA
Forward surge current	60Hz half-sine wave, 1cycle,T₂=25°C	I <sub>FSM</sub>	60	А
Reverse surge current	W <sub>P</sub> =1ms, Rectangular-wave, One- shot, T <sub>a</sub> =25°C	I <sub>RSM</sub>	100	mA
Peak forward voltage	I <sub>FM</sub> =450mA	V <sub>FM</sub>	≤12	v
Peak reverse current	V <sub>RM</sub> =V <sub>RRM</sub>	I <sub>RRM1</sub>	≤5	μΑ
Avalanche breakdown voltage	Ι <sub>R</sub> =100μΑ	V (BR)	≥16.5	kV
Virtual junction temperature		T <sub>(vj)</sub>	130	°C
Storage temperature		T <sub>stg</sub>	-40 ~ +130	°C

Notes: Cooling Requirement: Cathode terminal is fastened to radiating fin that size is more than 50mm×50mm×0.6mm Wind-cooled velocity is more than 0.5m/s




## **Ordering information**

Package	Packing Description	Packing Quantity
DO-722 bulk		500PCS/Inner Bag 4000PCS/Carton

## Package Dimensions(Millimeter(mm)

DO-722





# Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <a href="https://www.yfwdiode.com">https://www.yfwdiode.com</a>, or consult YFW sales office for further assistance.