

Schottky Barrier Diodes

FEATURES

- ◆For surface mounted applications
- ◆Low Forward Voltage Drop
- ◆Fast Switching
- ◆Small Surface Mount Package
- ◆PN Junction Guard Ring for Transient and ESD Protection
- ◆Available in Lead Free Version

Pinning

1.Cathode	2.Anode
	
SOD-123	

Marking Code

BAT54W	S1
--------	----


Absolute Maximum Ratings Ta = 25 °C

Parameter	Symbols	Limit	Units
DC blocking voltage	V_R	30	V
RMS reverse voltage	$V_{R(RMS)}$	21	
Average rectified output current	V_{RMS}	100	mA
Forward continuous current	I_F	200	mA
Repetitive peak forward current	I_{FRM}	300	mA
Non-repetitive Peak Forward Surge Current @t=8.3mS	I_{FSM}	600	mA
Power Dissipation	P_d	500	mW
Thermal resistance junction to ambient	$R_{\theta JA}$	200	°C/W
Junction temperature	T_j	125	°C
Storage temperature range	T_{stg}	-55~+150	°C


Electrical Characteristics Ta = 25 °C

Parameter	Symbols	Conditions	Min	Typ	Max	Units
Reverse breakdown voltage	$V_{(BR)}$	$I_R=100\mu A$	30	-	-	V
Forward voltage	V_{F1}	$I_F=0.1mA$	-	-	240	mV
	V_{F2}	$I_F=1.0mA$	-	-	320	
	V_{F3}	$I_F=10mA$	-	-	400	
	V_{F4}	$I_F=30mA$	-	-	500	
	V_{F5}	$I_F=100mA$	-	-	1000	
Reverse current	I_R	$V_R=25V$	-	-	2.0	uA
Reverse recovery time	T_{rr}	$I_F=10mA, I_R=10mA$ to 1mA , $R_L=100\Omega$	-	-	5.0	nS
Capacitance between terminals	C_T	$V_R=1V, f=1MHz$	-	-	10	pF


Forward Characteristics




Reverse Characteristics



Capacitance Characteristics



Power Derating Curve



Ordering information


Package	Packing Description	Packing Quantity
SOD-123	Tape/Reel, 7" reel	3000PCS/Reel 120000PCS/Carton

Package Dimensions

SOD-123

Dim.	Millimeter(mm)		mil	
	Min.	Max.	Min.	Max.
A	0.9	1.3	35	51
C	0.09	0.22	3.5	8.7
D	1.5	1.8	59	71
E	2.5	2.8	98	110
E1	3.6	3.9	142	154
b	0.5	0.7	20	28
L1	0.25	0.45	10	18
A1	-	0.2	-	8
∠	9°			

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.