


NPN Plastic-Encapsulate Transistors

Medium Power Linear and Switching Applications

◆Complement to BD434, BD436 and BD438 respectively



TO-126

Absolute Maximum Ratings (Ta=25℃)

Parameter		Symbol	Value	Unit
Collector-Base Voltage	BD433	BV_{CBO}	22	V
	BD435		32	
	BD437		45	
Collector-Emitter Voltage	BD433	BV_{CEO}	22	V
	BD435		32	
	BD437		45	
Emitter-Base Voltage		BV_{EBO}	5	V
Collector Current (DC)		I_C	4	A
Collector Current(Pulse) *		I_{CP}	7	A
		I_B	1	A
Collector Power Dissipation		P_C	1.25	W
Junction Temperature		T_j	150	℃
Storage Temperature		T_{stg}	-55~150	℃

Electrical Characteristics (Ta=25°C)

Parameter		Symbol	Conditions	Value			Unit
				Min	Typ	Max	
Collector-base breakdown voltage	BD433 BD435 BD437	BV_{CBO}	$I_C = 100\mu A, I_E = 0$	22 32 45			V
Collector-emitter breakdown voltage	BD433 BD435 BD437	BV_{CEO}	$I_C = 10mA, I_B = 0$	22 32 45			V
Emitter-base breakdown voltage		BV_{EBO}	$I_E = 100\mu A, I_C = 0$	5			V
Collector cut-off current	BD433 BD435 BD437	I_{CBO}	$V_{CB} = 22V, I_E = 0$ $V_{CB} = 32V, I_E = 0$ $V_{CB} = 45V, I_E = 0$			100	μA
Collector cut-off current	BD433 BD435 BD437	I_{CEO}	$V_{CE} = 22V, V_{BE} = 0$ $V_{CE} = 32V, V_{BE} = 0$ $V_{CE} = 45V, V_{BE} = 0$			100	μA
Emitter cut-off current		I_{EBO}	$V_{EB} = 5V, I_C = 0$			100	μA
DC current gain*		h_{FE}	$V_{CE} = 5V, I_C = 10mA$ $V_{CE} = 1V, I_C = 0.5A$ $V_{CE} = 1V, I_C = 2A$	30 85 40		140 140	
Collector-emitter saturation voltage*		$V_{CE(sat)}$	$I_C = 2A, I_B = 0.2A$		0.2	0.5	V
Base -emitter saturation voltage*		$V_{BE(on)}$	$V_{CE} = 1V, I_C = 2A$			1.1	V
Transition frequency		f_T	$V_{CE} = 1V, I_B = 250mA$	3			MHz

* Pulse Test: PW=300 μ s, duty Cycle=1.5% Pulsed

Typical Characteristics




Figure 1. DC current Gain




Figure 2. Collector-Emitter Saturation Voltage




Figure 3. Base-Emitter On Voltage




Figure 4. Collector-Base Capacitance




Figure 5. Safe Operating Area





Figure 6. Power Derating

Ordering information

Package	Packing Description	Base Quantity
TO-126	Bulk	500pcs/Bag

Package Dimensions

TO-126

	Symbol	Millimeter		Inches	
		Min.	Max.	Min.	Max.
	A	2.40	2.80	0.094	0.110
	A1	1.00	1.40	0.039	0.055
	b	0.66	0.86	0.026	0.034
	b1	1.17	1.37	0.046	0.054
	c	0.40	0.60	0.016	0.024
	D	7.30	7.70	0.287	0.303
	E	10.60	11.00	0.417	0.433
	e	2.25	2.33	0.089	0.092
	e1	4.50	4.66	0.177	0.183
	L	14.00	15.00	0.551	0.591
	L1	1.90	2.50	0.075	0.098
	Φ	3.10	3.30	0.122	0.130

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.