


**SIC SCHOTTKY BARRIER DIODE**

**Reverse Voltage - 1200 V**

**Forward Current - 10A**



**FEATURES**

- ◆1200V Schottky Rectifier
- ◆Zero Reverse Recovery Current
- ◆High-Frequency Operation
- ◆Temperature-Independent Switching Behavior
- ◆Extremely Fast Switching

**APPLICATIONS**

- ◆Replace Bipolar with Unipolar Rectifiers
- ◆Essentially No Switching Losses
- ◆Higher Efficiency
- ◆Reduction of Heat Sink Requirements
- ◆Parallel Devices Without Thermal Runaway

**BENEFITS**

- ◆High-speed switching
- ◆Low heat dissipation requirements
- ◆Reduced EMI
- ◆High-reliability

**Maximum Ratings at Ta=25°C unless otherwise specified**

Parameter	Test Conditions	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	T <sub>C</sub> = 25°C	V <sub>RRM</sub>	1200	V
Continuous Forward Current for Rth(j-c,max)	T <sub>C</sub> = 25°C	I <sub>F</sub>	37	A
	T <sub>C</sub> = 135°C		18	
	T <sub>C</sub> = 150°C		10	
Non-Repetitive Forward Surge Current, Sine Half-Wave	T <sub>C</sub> = 25°C, tp = 10ms	I <sub>FSM</sub>	52	A
	T <sub>C</sub> = 110°C, tp = 10ms		43	
Repetitive Forward Surge Current, Sine Half-Wave	T <sub>C</sub> = 25°C, tp = 10ms	I <sub>FRM</sub>	75	A
	T <sub>C</sub> = 110°C, tp = 10ms		62	
Power Dissipation	T <sub>C</sub> =25°C	P <sub>tot</sub>	234	W
	T <sub>C</sub> =110°C		102	
Operating Temperature Range	-	T <sub>J</sub>	-55 to +175	°C
Storage Temperature Range	-	T <sub>STG</sub>	-55 to +175	°C
Typical Thermal Resistance (Note1)	-	R <sub>θJC</sub>	0.64	°C/W

**Note1:Pulse test: 300 μs pulse width, 2 % duty cycle**

**Electrical Characteristics unless otherwise specified**

Parameter		Symbol	Value			Unit
			Min	Typ	Max	
Forward Voltage Drop(Note2)		<b>V<sub>bc</sub></b>	1200	-	-	<b>V</b>
$I_R = 100\mu A$						
at $I_F = 10A$	$T_A = 25^\circ C$	<b>V<sub>F</sub></b>	-	1.4	1.8	<b>V</b>
	$T_A = 175^\circ C$		-	2.1	3	
Maximum Reverse Current at $V_R = 1200V$	$T_A = 25^\circ C$	<b>I<sub>R</sub></b>	-	2.4	250	<b><math>\mu A</math></b>
	$T_A = 175^\circ C$		-	73	350	
Total capacitive charge	$V_R = 800V$	<b>Q<sub>c</sub></b>	-	51	-	<b>nC</b>
Total capacitance	$V_R = 0V, f = 1MHz$	<b>C</b>	-	770	-	<b>pF</b>
	$V_R = 400V, f = 1MHz$		-	47	-	
	$V_R = 800V, f = 1MHz$		-	46	-	
Capacitance stored energy	$V_R = 800V$	<b>E<sub>c</sub></b>	-	12.6	-	<b><math>\mu J</math></b>

**Note2:Pulse test: 300  $\mu s$  pulse width, 1 % duty cycle**

RATINGS AND CHARACTERISTIC CURVES




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics




Figure 3. Current Derating




Figure 4. Power Derating

RATINGS AND CHARACTERISTIC CURVES




Figure 5. Capacitance Charge Vs. Reverse Voltage




Figure 6. Capacitance Vs. Reverse Voltage




Figure 7. Capacitance Stored Energy





Figure 8. Transient Thermal Response Curve(Junction-to-Case)

**Marking Diagram**



**Ordering information**

Model name	Package	Unit Weight	Base Quantity	Packing Quantity
YFWD310120FAC	TO-220FAC	0.06oz(1.7g)	50pcs/tube	1000PCS/Box 5000PCS/Carton

**Package Dimensions**

**TO-220FAC**

Symbol	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	9.95	10.25	0.392	0.404
B	2.95	3.25	0.116	0.128
C	1.25	1.45	0.049	0.057
E	12.95	13.25	0.51	0.52
F	0.40	0.60	0.016	0.024
G	1.30	1.45	0.051	0.057
H	TYP2.54		TYP 0.1	
I	TYP5.08		TYP 0.2	
J	4.60	4.75	0.181	0.187
K	2.45	2.65	0.097	0.104
L	6.5	6.8	0.256	0.268
M	15.4	16.0	0.606	0.630
N	2.75	3.05	0.108	0.120
O	0.45	0.55	0.018	0.022
P	0.6	0.8	0.024	0.032
Q	0.76	0.84	0.030	0.033

## Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.